

MATERIALI ECOLOGICI PER L'EDILIZIA

Breathable painting made up of lime putty

DATA SHEET

Container:

18 kg.

Composition of the product:

Lime putty, glue and ecological natural earth.

Dilution:

Ready to use.

Features:

Highly breathable.

Diluent:

Water.

Estimated consumption:

300g/sqm. in one coat.

Usage: Inside/outside.

Background preparation::Before applying TOP, it is advisable to apply on the wall our Isoltop, for a better insulation and grip of the product. The wall surface must be completely free of dust and dirt and any traces of oils, fats, waxes, which must be removed by brushing or sanding the surface.

Application: Apply TOP paint with a brush.

Storage: The material is preserved for 12 months from the date of production, in sealed containers, provided that they are not exposed to frost or heat sources. The applicator must not modify the product, in that case ET Events & Technologies S.r.l.s assumes no responsibility.





H318 Causes serious eye damage

P301+330+331IN CASE OF INGESTION: rinse your mouth. DO NOT cause vomit P305+P351+P338 IN CASE OF CONTACT WITH EYES: rinse accurately for several minutes. Remove thelenses

ET Events & Technologies s.r.l.s. - Via Circonvallazione 22, Cassolnovo (PV) - Tel.0381 090518 - www.etgc.it